




892

Material Viton/Butyl LENGTH 12 in. / 300mm



CHEMICAL PERMEATION

CHEMICAL NAME	CAS NUMBER	BDT
		TTL EN374
Chloride, Methylene	75-09-2	>30
Benzene, Methyl	108-88-3	>480
Battery Acid 50%	7664-93-9	>480
Battery Acid 93%	7664-93-9	>480
Battery Acid 96%	7664-93-9	>480
Battery Acid 70%	7664-93-9	>480
Battery Acid 10%	7664-93-9	>480
Battery Acid 25%	7664-93-9	>480

**BDT=BREAKTHROUGH DETECTION TIME**

THE LEVEL (0 TO 6) INDICATES THE TIME REQUIRED FOR DIFFERENT CHEMICALS TO PERMEATE THROUGH THE GLOVE.

TTL : TOTAL IMMERSION CHEMICAL PERMEATION BREAKTHROUGH TIME.

INT : INTERMITTENT CONTACT CHEMICAL PERMEATION BREAKTHROUGH TIME, ONE MINUTE IMMERSION OUT OF EVERY TEN, REPEATEDLY.

**Warranty Limitations and Disclaimer Use**

This information is provided solely as a convenience to help you evaluate our gloves in the end-user's particular application. It is the responsibility of the purchaser and/or user to determine the level of toxicity of the materials to be handled and to select the proper glove suitable for a particular application. The information provided reflects laboratory performance of gloves under carefully controlled conditions. SHOWA makes no guarantee of results and assumes no obligation or liability in connection with this information.